

PDP mini - łyżka ażurowa do kamieni w profilu BDP

Modele i dane techniczne

Model	Klasa maszyny [t]	Szerokość [mm]	Wysokość [mm]	Długość [mm]	Pojemność SAE [dm³]	Promień końcówki [mm]	Mocowania szybkozłączna	Masa [kg]
PDP-10	0,6-1,2	400	347	416	32	330	CW00	26
PDP-10	0,6-1,2	600	347	416	52	330	CW00	38
PDP-20	1,2-1,8	400	412	460	40	384	CW05	32
PDP-20	1,2-1,8	600	412	460	66	384	CW05	45
PDP-20	1,2-1,8	700	412	460	79	384	CW05	50
PDP-30	1,8-2,5	600	484	520	93	448	CW05	53
PDP-30	1,8-2,5	700	484	520	112	448	CW05	60
PDP-30	1,8-2,5	800	484	520	130	448	CW05	66
PDP-40	2,5-4,0	600	570	628	129	532	CW05	75
PDP-40	2,5-4,0	700	570	628	154	532	CW05	83
PDP-40	2,5-4,0	800	570	628	182	532	CW05	91
PDP-40	2,5-4,0	1000	570	628	232	532	CW05	107
PDP-60	4,0-6,0	700	643	685	187	597	CW10	101
PDP-60	4,0-6,0	800	643	685	219	597	CW10	111
PDP-60	4,0-6,0	1000	643	685	283	597	CW10	128
PDP-75	6,0-7,5	700	709	791	229	670	CW10	128
PDP-75	6,0-7,5	800	709	791	268	670	CW10	143
PDP-75	6,0-7,5	1000	709	791	350	670	CW10	166
PDP-90	7,5-10	800	816	875	344	780	CW10	163
PDP-90	7,5-10	1000	816	875	442	780	CW10	187
PDP-90	7,5-10	1200	816	875	546	780	CW10	209

Wartości zgodne z kartą katalogową tej rodziny. Myślnik oznacza, że karta nie podaje tej wartości.